



江苏通路新材料科技股份有限公司
Terou New Material Technology Co., Ltd

Perforated raised floor - Air Flow Panel						
Type	International Standard	Size (mm)	Concentrated Load (N)	Uniform Load (N)	Ultimate Load (N)	Deflection (mm)
TLSP-8001	FS440	600*600mm 35-55mm thickness	1960	9720	5880	≤2
TLSP-8002	FS662		2950	12500	8850	≤2
TLSP-8003	FS800		3550	16100	11250	≤2
TLSP-8004	FS1000		4450	23000	13350	≤2
TLSP-8005	FS1250		5560	33000	16680	≤2
TLSP-8006	FS1500		6675	34500	19892	≤2
TLSP-8007	FS2000		8890	44450	29420	≤2
TLSP-8008	FS2500		11110	57790	37340	≤2
TLSP-8009	FS3000		13630	68150	49890	≤2
1. Ventilation Rate available: 0%, 17%, 20%, 22%, 25%, 29%, 35%, 46%, 50%, 55%, 70% etc. 2. Customization is available. 3. Corner lock hole type is available. 4. Epoxy coating. 5. HPL, PVC, SUS304 covering.						

ADD: No.33 Xingchen Road, Hengshanqiao Industrial Park, Changzhou, Jiangsu, China.

TEL: 0086 15961179799



WHATSAPP: 0086 15961179799



WECHAT: 0086 15961179799

WEB: www.tongluraisedfloor.com

EMAIL: andy@tongluraisedfloor.com